




Rollagate

350


800



703 TOP GUIDE ROLLER



104/99 TOP GUIDE ROLLER



53/99 TOP GUIDE ROLLER

Maximum gate weight	350kg	800kg
Gate thickness	44-54mm	51-63mm
Minimum gate thickness – metal	50mm	60mm

TOP GUIDE CHANNEL

	Ref. No.	Price \$	Ref. No.	Price \$
2000mm galvanised steel – drilled & countersunk	99-20	86.80	99-20	86.80
3000mm galvanised steel – drilled & countersunk	99-30	130.00	99-30	130.00
4000mm galvanised steel – drilled & countersunk	99-40	173.40	99-40	173.40

TOP GUIDE BRACKETS

Face fitted – intermediate – single run	31	12.50	31	12.50
Face fitted – jointing – single run	31X	14.90	31X	14.90

TOP GUIDE ROLLERS

For timber gate – use with top guide channel	53/99	37.80	53/99	37.80
For metal gate – use with top guide channel	104/99	31.90	104/99	31.90
For timber or metal gates – use without top guide channel	703	128.60	703	128.60

BOTTOM ROLLERS

For timber gate	2	152.20	3	250.80
For metal gate	1S	136.60	3S	205.60

ACCESSORIES

Flush pull – aluminium	414	12.00	414	12.00
Door stop – wall or floor mounted	109	19.40	109	19.40
Door stop – wall mounted steel zinc plate	107	22.50	107	22.50

